

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : SHAMPOO SAPHIR SPRAY  
Product code : 0525023  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use  
Use of the substance/mixture : Shoe and leather care product. Textile care product.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

AVEL  
Lombre  
MAGNAC LAVALETTE  
16320  
FRANCE  
T +33(0) 545 647 474, F +33(0) 545 647 736  
[brigitte-terrien@avel.com](mailto:brigitte-terrien@avel.com)

#### 1.4. Emergency telephone number

Emergency number : +33(0) 476 753 045

| Country/Area | Organisation/Company | Address               | Emergency number                                                                           | Comment |
|--------------|----------------------|-----------------------|--------------------------------------------------------------------------------------------|---------|
| US/CANADA    | 24/7 CHEMTREC        | chemtrec@chemtrec.com | 1(800) 424-9300<br>For Chemical Emergency ONLY (spill, leak, fire, exposure, or accident). |         |

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP)

: Danger

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

|                                |                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard statements (CLP)        | : H222 - Extremely flammable aerosol.<br>H229 - Pressurised container: May burst if heated.                                                                                                                                                                                                                                                              |
| Precautionary statements (CLP) | : P102 - Keep out of reach of children.<br>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P211 - Do not spray on an open flame or other ignition source.<br>P251 - Do not pierce or burn, even after use.<br>P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. |

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                                                           | Product identifier                                                  | %       | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------|-----------------------------------------------------------------|
| Propan-2-ol<br>substance with national workplace exposure limit(s)<br>(DE, ES, FR, GB, PT, SE) | CAS-No.: 67-63-0<br>EC-No.: 200-661-7<br>EC Index-No.: 603-117-00-0 | 1 – 3   | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336     |
| DisodiumC-(2-alkylamidoethyl)sulfosuccinate                                                    | CAS-No.: 68784-08-7<br>EC-No.: 272-219-1                            | 0,1 – 3 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319                       |

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                                       |                                                                  |
|---------------------------------------|------------------------------------------------------------------|
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water.                                |
| First-aid measures after eye contact  | : Rinse eyes with water as a precaution.                         |
| First-aid measures after ingestion    | : Call a poison center or a doctor if you feel unwell.           |

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
|------------------------------|--------------------------------------------------|

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 5.2. Special hazards arising from the substance or mixture

|                                                  |                                               |
|--------------------------------------------------|-----------------------------------------------|
| Fire hazard                                      | : Extremely flammable aerosol.                |
| Explosion hazard                                 | : Pressurised container: May burst if heated. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released.                |

### 5.3. Advice for firefighters

|                                |                                                                                                                                          |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

|                      |                                                                       |
|----------------------|-----------------------------------------------------------------------|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. |
|----------------------|-----------------------------------------------------------------------|

#### 6.1.2. For emergency responders

|                      |                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Methods for cleaning up | : Mechanically recover the product.                             |
| Other information       | : Dispose of materials or solid residues at an authorized site. |

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

|                               |                                                                                                                                                                                                                                                                                  |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautions for safe handling | : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. |
| Hygiene measures              | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.                                                                                                                                                                              |

### 7.2. Conditions for safe storage, including any incompatibilities

|                    |                                                                                                                              |
|--------------------|------------------------------------------------------------------------------------------------------------------------------|
| Storage conditions | : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool. |
|--------------------|------------------------------------------------------------------------------------------------------------------------------|

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Propan-2-ol (67-63-0)                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| France - Occupational Exposure Limits             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local name                                        | Alcool isopropylique                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| VLE (OEL C/STEL)                                  | 980 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                   | 400 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Germany - Occupational Exposure Limits (TRGS 900) |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local name                                        | Propan-2-ol                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| AGW (OEL TWA)                                     | 500 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                   | 200 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Remark                                            | DFG,Y                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Portugal - Occupational Exposure Limits           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local name                                        | 2-Propanol (isopropanol ou álcool isopropílico)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| OEL TWA                                           | 200 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OEL STEL                                          | 400 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Spain - Occupational Exposure Limits              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local name                                        | Isopropanol (Alcohol isopropílico)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| VLA-ED (OEL TWA)                                  | 500 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                   | 200 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| VLA-EC (OEL STEL)                                 | 1000 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                                   | 400 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Remark                                            | (2011), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para unainformación detallada acerca de las prohibiciones consúltese:Base de datos de productos biocidas: <a href="http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas">http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas</a> Base de datos de productos fitosanitarios: <a href="http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf">http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf</a> ) |
| Sweden - Occupational Exposure Limits             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local name                                        | Isopropanol                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| NGV (OEL TWA)                                     | 350 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                   | 150 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| KGV (OEL STEL)                                    | 600 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                   | 250 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| United Kingdom - Occupational Exposure Limits     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Local name                                        | Propan-2-ol                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| WEL TWA (OEL TWA)                                 | 999 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                   | 400 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| WEL STEL (OEL STEL)                               | 1250 mg/m³                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                                   | 500 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

### 8.1.2. Recommended monitoring procedures

No additional information available

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

**Personal protective equipment symbol(s):**



#### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

#### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

#### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                           |                                               |
|---------------------------|-----------------------------------------------|
| Physical state            | : Liquid                                      |
| Colour                    | : Not available                               |
| Odour                     | : Not available                               |
| Odour threshold           | : Not available                               |
| Melting point             | : Not applicable                              |
| Freezing point            | : Not available                               |
| Boiling point             | : 90 °C                                       |
| Flammability              | : Extremely flammable aerosol.                |
| Explosive properties      | : Pressurised container: May burst if heated. |
| Lower explosion limit     | : Not available                               |
| Upper explosion limit     | : Not available                               |
| Flash point               | : 23 °C                                       |
| Auto-ignition temperature | : Not available                               |

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

|                                                 |                  |
|-------------------------------------------------|------------------|
| Decomposition temperature                       | : Not available  |
| pH                                              | : Not available  |
| Viscosity, kinematic                            | : Not available  |
| Solubility                                      | : Not available  |
| Partition coefficient n-octanol/water (Log Kow) | : Not available  |
| Vapour pressure                                 | : Not available  |
| Vapour pressure at 50°C                         | : Not available  |
| Density                                         | : Not available  |
| Relative density                                | : Not available  |
| Relative vapour density at 20°C                 | : Not available  |
| Particle characteristics                        | : Not applicable |

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 8,00468 %

#### 9.2.2. Other safety characteristics

VOC content : 2,547 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

|                                   |                  |
|-----------------------------------|------------------|
| Acute toxicity (oral)             | : Not classified |
| Acute toxicity (dermal)           | : Not classified |
| Acute toxicity (inhalation)       | : Not classified |
| Skin corrosion/irritation         | : Not classified |
| Serious eye damage/irritation     | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity            | : Not classified |
| Carcinogenicity                   | : Not classified |

#### Propan-2-ol (67-63-0)

|                       |                      |
|-----------------------|----------------------|
| IARC group            | 3 - Not classifiable |
| Reproductive toxicity | : Not classified     |
| STOT-single exposure  | : Not classified     |

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Propan-2-ol (67-63-0)

|                        |                                    |
|------------------------|------------------------------------|
| STOT-single exposure   | May cause drowsiness or dizziness. |
| STOT-repeated exposure | : Not classified                   |
| Aspiration hazard      | : Not classified                   |

### SHAMPOO SAPHIR SPRAY

|           |         |
|-----------|---------|
| Vaporizer | Aerosol |
|-----------|---------|

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                                                                                         |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Ecology - general                                         | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified                                                                                                        |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified                                                                                                        |

### 12.2. Persistence and degradability

#### SHAMPOO SAPHIR SPRAY

|                               |                    |
|-------------------------------|--------------------|
| Persistence and degradability | Rapidly degradable |
|-------------------------------|--------------------|

#### DisodiumC-(2-alkylamidoethyl)sulfosuccinate (68784-08-7)

|                               |                    |
|-------------------------------|--------------------|
| Persistence and degradability | Rapidly degradable |
|-------------------------------|--------------------|

#### Propan-2-ol (67-63-0)

|                               |                    |
|-------------------------------|--------------------|
| Persistence and degradability | Rapidly degradable |
|-------------------------------|--------------------|

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                         |                                                                                               |
|-------------------------|-----------------------------------------------------------------------------------------------|
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
|-------------------------|-----------------------------------------------------------------------------------------------|

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

#### 14.1. UN number or ID number

|               |           |
|---------------|-----------|
| UN-No. (ADR)  | : UN 1950 |
| UN-No. (IMDG) | : UN 1950 |
| UN-No. (IATA) | : UN 1950 |
| UN-No. (ADN)  | : UN 1950 |
| UN-No. (RID)  | : UN 1950 |

#### 14.2. UN proper shipping name

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Proper Shipping Name (ADR)            | : AEROSOLS                         |
| Proper Shipping Name (IMDG)           | : AEROSOLS                         |
| Proper Shipping Name (IATA)           | : Aerosols, flammable              |
| Proper Shipping Name (ADN)            | : AEROSOLS                         |
| Proper Shipping Name (RID)            | : AEROSOLS                         |
| Transport document description (ADR)  | : UN 1950 AEROSOLS, 2.1, (D)       |
| Transport document description (IMDG) | : UN 1950 AEROSOLS, 2.1            |
| Transport document description (IATA) | : UN 1950 Aerosols, flammable, 2.1 |
| Transport document description (ADN)  | : UN 1950 AEROSOLS, 2.1            |
| Transport document description (RID)  | : UN 1950 AEROSOLS, 2.1            |

#### 14.3. Transport hazard class(es)

##### ADR

|                                  |       |
|----------------------------------|-------|
| Transport hazard class(es) (ADR) | : 2.1 |
| Danger labels (ADR)              | : 2.1 |
|                                  | :     |



##### IMDG

|                                   |       |
|-----------------------------------|-------|
| Transport hazard class(es) (IMDG) | : 2.1 |
| Danger labels (IMDG)              | : 2.1 |
|                                   | :     |



##### IATA

|                                   |       |
|-----------------------------------|-------|
| Transport hazard class(es) (IATA) | : 2.1 |
| Danger labels (IATA)              | : 2.1 |
|                                   | :     |



##### ADN

|                                  |       |
|----------------------------------|-------|
| Transport hazard class(es) (ADN) | : 2.1 |
| Danger labels (ADN)              | : 2.1 |
|                                  | :     |



##### RID

|                                  |       |
|----------------------------------|-------|
| Transport hazard class(es) (RID) | : 2.1 |
|----------------------------------|-------|



# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danger labels (RID) : 2.1  
:



### 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable  
Packing group (ADN) : Not applicable  
Packing group (RID) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2  
Tunnel restriction code (ADR) : D

#### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

#### Air transport

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

#### Inland waterway transport

Classification code (ADN) : 5F  
Special provisions (ADN) : 190, 327, 344, 625  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

### Rail transport

Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P207, LP200  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage – Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

##### VOC Directive (2004/42)

VOC content : 2,547 %

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

# SHAMPOO SAPHIR SPRAY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 15.1.2. National regulations

#### France

| Occupational diseases |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code                  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| RG 84                 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

#### Germany

|                                            |                                                                                                                                                                                       |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Employment restrictions                    | : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).<br>Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG). |
| Water hazard class (WGK)                   | : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).                                                                                                       |
| Hazardous Incident Ordinance (12. BImSchV) | : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)                                                                                                                    |

#### Netherlands

|                                                         |                                                         |
|---------------------------------------------------------|---------------------------------------------------------|
| SZW-lijst van kankerverwekkende stoffen                 | : DisodiumC-(2-alkylamidoethyl)sulfosuccinate is listed |
| SZW-lijst van mutagene stoffen                          | : DisodiumC-(2-alkylamidoethyl)sulfosuccinate is listed |
| SZW-lijst van reprotoxische stoffen – Borstvoeding      | : None of the components are listed                     |
| SZW-lijst van reprotoxische stoffen –<br>Vruchtbaarheid | : None of the components are listed                     |
| SZW-lijst van reprotoxische stoffen – Ontwikkeling      | : None of the components are listed                     |

#### Denmark

|                             |                                                                                                          |
|-----------------------------|----------------------------------------------------------------------------------------------------------|
| Class for fire hazard       | : Class II-1                                                                                             |
| Store unit                  | : 5 liter                                                                                                |
| Classification remarks      | : R10 <H222;H229>; Emergency management guidelines for the storage of flammable liquids must be followed |
| Danish National Regulations | : Young people below the age of 18 years are not allowed to use the product                              |

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

| Full text of H- and EUH-statements: |                                                                        |
|-------------------------------------|------------------------------------------------------------------------|
| Eye Irrit. 2                        | Serious eye damage/eye irritation, Category 2                          |
| Flam. Liq. 2                        | Flammable liquids, Category 2                                          |
| H222                                | Extremely flammable aerosol.                                           |
| H225                                | Highly flammable liquid and vapour.                                    |
| H229                                | Pressurised container: May burst if heated.                            |
| H315                                | Causes skin irritation.                                                |
| H319                                | Causes serious eye irritation.                                         |
| H336                                | May cause drowsiness or dizziness.                                     |
| Skin Irrit. 2                       | Skin corrosion/irritation, Category 2                                  |
| STOT SE 3                           | Specific target organ toxicity – Single exposure, Category 3, Narcosis |

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.